

# TASKalfa 5053ci

COLOUR MULTIFUNCTIONAL FOR A4/A3 (SRA3) FORMAT

# SECURE EFFICIENCY



Providing the latest in security technology to protect all valuable data, the new TASKalfa 5053ci ensures that information is kept under virtual lock and key. Using added features to secure information means that companies can use their multifunctional product safe in the knowledge that they are not putting invaluable data at risk in the process. Furthermore, vibrant colour ensures high quality printing alongside a flexible approach to paper-handling and finishing, meaning that the TASKalfa device is the complete solution to provide an efficient way to print, copy and scan whilst relying on an award-winning engine. With all of these features put together, the ideal solution is available to manage office document needs.

- > Up to 50/25 pages A4/A3 per minute in colour
- > Outstanding image quality due to advanced colour technology
- > User friendly and intuitive 10.1 inch operation panel
- > Advanced paper handling from A6 up to SRA3 for up to 7,150 sheets
- > Great range of high speed colour scanners and productive finishing options
- > High-level build in security features including data encryption, Trusted Platform Module, Secure Boot and Run Time Integrity Check
- > Long-life components providing exceptional efficiency and reliability, and less waste
- > Optional Fiery Controller for highest productivity and colour quality





Data security has become a top priority for every business today. The new TASKalfa 5053ci includes high-level security features to enhance the privacy

of your printing environment.

#### GENERAL

Technology: KYOCERA TASKalfa Laser Colour, HyPAS solution platform Touch panel size: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel mounted

Engine speed (pages per minute): Duplex print speed: 50 ppm A4; Duplex copy speed: 50 ppm, A4 Resolution: 4800dpi equivalent x 1200dpi (print), 600 x

600 dpi (scan/copy) Warm-up time from power on: Approx. 17 seconds or less Time to first print: 4.3 / 5.4 seconds or less

in b/w / colour Time to first copy: 4.5/ 6.5 seconds or less in b/w / colour (DP); 3.7/ 4.8 seconds or less in b/w / colour (Platen)

CPU: OorIO T1024 (Dual Core) 1.2GHz Memory (standard max.): 4 GB RAM + 8 GB SSD + 320 GB HDD

Standard interface: Standard interface: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Etherne (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, (10BaseT/100BaseTX/1000BaseT, IPvG, IPv4, IPSec, 802.3az support), optional Wi-FI (IEEE 802.11b/g/n), 2 eKUIO Slots, for optional linternal print server or for optional fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag Dimensions (W a D x H): Main unit: 602 x 665 x 790 mm Weight: Main unit: Approx. 95 kg Power consumption: Printing: 900 W Copying: 900 W Ready mode: 60 W Low power mode: 50 W Sleep mode: 0.7 W

# Noise (sound pressure level ISO 7779 measurement distance of 1 meter): Copying/Printing: 53.3 dB (A) in colour Stand-by: 35 dB (A)

Safety standards: GS, TÜV, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

#### PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: Multipurpose tray: 150 sheets, 52–300 g/m² (Banner 136 – 163 g/m²), A6R – SRA3 (320 x 450 mm), Custom (98 x 148 to 297 x 457.2 mm), Banner max. 304.8 x 1,220 mm; Standard universal paper cassette: 2 x 500 sheets,

52 – 300 g/m², Upper cassette A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4

Duplex unit: Duplex as standard supports AGR – SRA3, 64 – 256 g/m<sup>2</sup> Output capacity: Standard 500 sheets face-down, max. output capacity 4,300 sheets

#### PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS

Operating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional based of the system dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec,SNMPv3, quick copy, proof and hold, private print, job storage functionality

Mobile printing support: KYOCERA Mobile Print app for

#### **KYOCERA Document Solutions Australia** Phone: 13 5962

kyoceradocumentsolutions.com.au

iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

#### COPY FUNCTIONS

Max. original size: A3 / Ledger Continuous copying: 1–9999 Zoom range: 25–400% in 1% steps Preset magnification ratios: 5R/5E, Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo, Diagram/map Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy

#### SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB, Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD

scan Scan speed: 220 images per minute (300 dpi, A4 duplex, with DP-7130) in b/w and colour

With DP-7130 In D/W and Colour Scan resolution: 600dpi x 600dpi, 400dpi x 400dpi , 200dpi x 400dpi, 300dpi x 300dpi, 200dpi x 200dpi, 200dpi x 100dpi, 256 greyscales per colour Max. scan size: A3, Ledger Original recognition: Text, photo, text + photo, Light Text / Eina Line activitiend for QCP.

File Line, optimised for OCR File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(option), MS Office file(option)

#### FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Compatibility: 110-1 Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Max. 3 seconds (JBIG) Scanning speed: 2.0 seconds or less Maximum original size: A3, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH Features: Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internet-fax, dual fax with second fax system 12

#### CONSUMABLES

Average continuous toner yield in accordance with 5%

TK-8519K Toner-Kit: Toner black for 30,000 pages A4 TK-8519K, Toner-Kit: Toner black for 30,000 pages A4 TK-8519C, TK-8519M, TK-8519Y Toner-Kits: Toner cyan, magenta, yellow for 20,000 pages WT-8500 Waste Toner Bottle: 40,000 sheets (in accord-pre with FW coverage b (unsclour = 7,2)

ance with 5% coverage b/w:colour = 7:3)

Staple cartridge: SH-10 5000 x 3 staples, for DF-7100, DF-7120 and BF-730 SH-12 5000 x 3 staples, for DF-7110 SH-14 5000 x 5 staples, for DF-7130

#### OPTIONS

### Fax System 12

Internet Fax Kit (A) Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx) Printing System 15: Fiery Controller Printing System Interface Kit 15: Interface board for Fiery aper handling

**DP-7100 Document processor:** (Reversing), 140 sheets.

35-160 g/m² (simplex), 50-120 g/m² (duplex), A6R-A3, Banner up to 1,900 mm

**DP-7110 Document processor:** (one-path duplex scanning) 270 sheets at 50 - 80 g/m<sup>2</sup>, 35 - 220 g/m<sup>2</sup> (simplex), 50 - 220 g/m<sup>2</sup> (duplex), A6R - A3, Banner up to 1,900 mm **DP-7130 Document processor:** (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50 - 80 g/m<sup>2</sup>, 35–220 g/m<sup>2</sup> (simplex), 50–220 g/m<sup>2</sup> (duplex), A6R–A3, Banner up to 1 900 mm

**DT-730(B) Document tray PF-7100 Paper feeder:** 2x 500 sheets, 52 – 300 g/m<sup>2</sup>, A6R – SRA3

PF-7110 Paper feeder: 2x 1,500 sheets, 52 - 300 g/m<sup>2</sup>, A4,

PF-7120 A4 side Deck: 3,000 sheets, 60 - 300 g/m<sup>2</sup>, A4, B5 **DF-7100 Inner finisher:** 500 sheets A4, 52–300 g/m<sup>2</sup>, A

# DF-7110<sup>\*</sup> Document finisher + AK-7110:

DF-710° Document finisher + AK-7110: Main tray: 4,000 sheets A4; Sub tray: 200 sheets A4; 52 – 300 g/m²; A6R – SRA3 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions DF-7120° Document finisher + AK-7110: 1,000 sheets A4, 52 – 300 g/m², A6R – SRA3, Stapling up to 50 sheets A4 or 30 sheets A3 at 3 position DF-7130° Document finisher + AK-7110: Main tray: 4,000 Sheets A4; Sub tray: 200 sheets 52–300 g/m² A6R–SRA3 Stapling up to 100 sheets A4 or 50 sheets A3 at 3 posi-tions

AK-7110 Attachment kit for DF-7110, DF-7120 and DF-7130, 100 sheets, 52–300 g/m<sup>2</sup>, A6R–SRA3, \* Bridge unit AK-7110 is required when using a finisher

PH-7C Punch unit for DF-7110/DF-7120/DF-7130: 2-hole/4-hole, 60 – 256 g/m<sup>2</sup>, A5R – A3 MT-730(B) Mailbox sorter for DF-7110:

**BF JP-710: 7** bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m<sup>2</sup> **BF-730 Booklet and tri-folding unit for DF-7110** Half-folding: 52-256 g/m<sup>3</sup>, A3, B4, A4R Booklet: Max. 16 sheets (64 pages, 60–90 g/m<sup>3</sup>) Non-staple folding: Max. 5 sheets (60–90 g/m<sup>2</sup>) Tri-folding: Max. 5 sheets (60–105 g/m<sup>2</sup>, A4R) With triticities c sheets (60–00 g/m<sup>2</sup>) A4R) Multi tri-folding: 5 sheets (60–90 g/m<sup>2</sup>), 3 sheets (91–105 g/m<sup>2</sup>) BF-9100 Booklet and tri-folding unit for DF-7130

Half-folding: 52–256 g/m², A3, B4, A4R Booklet : Max 20 sheets (80 pages, 60-90g/m²) or Max 13 sheets (52 pages 91-105g/m²)

Non-staple : Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m²) Tri-folding : Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m<sup>2</sup>)

# 100-sheet internal job separator, 52–300 g/m<sup>2</sup>, A5R–SRA3

PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher/ Swedish type

Banner Guide 10: Banner paper feeding guide, 10 sheets Keybordholder 10 NK-7120 Numeric keypad

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available. The card holder is standard

UG-33 AC: ThinPrint support UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630) Optional interface

## IB-35: Direct Wi-Fi Interface

**IB-50:** Gigabit-Ethernet board 10 BaseT/100 BaseTX/

1,000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

Platen cover (E) 1290: Cabinet for two drawer configuration



**KYOCERA Document Solutions New Zealand Ltd** Phone: 0800 459 623 kvoceradocumentsolutions.co.nz

KYOCERA Document Solutions New Zealand is the trading name of the New Zealand branch of KYOCERA Document Solutions Australia Pty Ltd a corporation incorporated in Australia

KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

